

MOTORIZED PAN/TILT MACHINE, GAC-PT1.

- One power supply for camera & pan/tilt.
- One remote controls for camera & pan/tilt.
- Infra-red(IR) wireless and wired remote controller may adjust of pan/tilt and tele/wide/focus of camera.
- Moving diagonally adjust by rotating limit buttons (right & left)
- Auto panning speed and range can be adjust by remocon unit(included)
- Motor & gear protection mechanism when panning motor is interrupted.
- More than 1km (3000ft) long distance operation

LVC-2701DN
(OPTIONAL)



GAC-PT1

REMOTE WINDOW



REMOTE WINDOW

SPECIFICATIONS FOR PAN/TILT, GAC-PT1

MODEL NO.	AC-PT1	AC-PT1-RS485
Power requirement	DC 12V, 0.5A (for pan/tilt)	
Power consumption	6 W	
Wired control range	1k meters max. (3000 feet)	
Horizontal panning range	310° for manual panning, 270° for auto panning	Same as GAC-PT1 with RS-485 communication system
Vertical tilting panning range	17° up, 27° down	
Horizontal panning speed	5.5°/sec for high speed mode, 3.7°/sec for low speed mode	
Vertical tilting speed	4°/sec	
Max loading	5 kg (11 pounds)	
Weight of unit	1.3kg (2.65 pounds)	"Remocon available by IR-200/RC-200"
Dimension of unit	Diameter : ϕ 136mm(5.35"), Height : 106mm(4.17")	

